

LOGISTIC VENDOR MANUAL FOR APPAREL, BAGS, ACCESSORIES



Contents

GENERAL SALEABLE UNIT PACKAGING	. 3
Master Carton	. 4
PRODUCT CARTON SPECIFICS	. 5
POLYBAG SPECIFICATION AND SUFFOCATION WARNING	. 6
DROP TEST:	. 7
PRESENTATION OF THE PACKAGING STRUCTURE:	. 7



NOTE:

at the link below, you can find some video content to go along with the logistics manuals that will be useful for the preparation of your goods:

https://corporate.qvc.it/wp-content/uploads/qvc-italy/2022/10/APPAREL-converted.mp4 (apparel date video content)

https://corporate.qvc.it/en-logistics/ (self help videos)

passw: qvc4info

GENERAL SALFABLE UNIT PACKAGING

Cut protection for master cartons is required. This does not affect the regulation for the product cartons.

QVC considers the packaging and labelling of product to be just as important as the quality of the actual item supplied: therefore, deliveries may be rejected for failure to comply with QVC's packaging requirements.

- The packaging of bulk stock must mirror either the sample provided to QVC QA or the information provided in the submitted specification card (spec card) and which received an accepted (or conditional) disposition.
- All packaging must be securely sealed to maintain the product within and prevent tampering.
- All open seams must be secured by means of tape using the "6-strip" or "H- pattern" taping
 method as this provides the most secure seal. Ideally this should be applied using a tape
 dispenser and should not cover the barcode label, wholly or in part. All corners must be
 sealed down as shown below.



• All voids should be filled with corrugated paper inserts and/or "crunch paper".



Corrugated paper



Crunch paper

• All cartons should be big enough that they remain cuboid once sealed.







- A set of two or more pieces, sold as one saleable unit, must be packaged in one single carton.
- Saleable unit cartons must be in a clean dust free condition.
- If the boxes containing the sales unit were to be wrapped in thermo-retracted film or sealed with heat-sealed polyethylene, it is necessary to take into consideration that, in the event of rework, they cannot be repackaged in the same way and that the costs will be charged to the vendor including material costs used to repackage the product.
- All warranties and other literature must be enclosed within the packaging.
- Product cartons that are oversized (longer than a pallet length) or that weigh more than 30 kg, require separate 2-man handling.

Master Carton

Master carton can have a MAXIMUM SIZE of 600mm length x 400mm width x 400mm.

If you saleable unit carton can be safely stacked directly into a pallet, respecting the wooden pallet size, then master cartons are not required, if this is not the case then the following carton requirements must be followed. We remind you that the master carton is required when the product is less then then the minimum master carton size required of **320mm length x 190mm width x 140mm**

QVC recommends that all open seams are secured by means of tape (self- adhesive polypropylene packaging tape 45mm wide) using the "6-strip" or "H- pattern" taping method as this provides the most secure seal. Ideally this should be applied using a tape dispenser and should not cover the barcode label, wholly or in part. ATTENTION! **No metal staple or straps are allowed.**

<u>Cut protection for master cartons is required</u>. This does not affect the regulation for the product cartons.

All voids should be filled with plain shredded card, bubble wrap, cardboard or polybag

Any partial cartons should have a label attached above the master carton label with the word "PARTIAL". This carton should be placed on the top layer of the pallet.

Minimum units per carton 2 and anything less please contact ltaly.SupplyChain.VendorManual@qvc.com

Affix the label at the top right/top left/ on the narrow side or affix in the center of the master carton and away from any clousure and on the external short side





Master carton must have just the QVC label applied. Any other labels are not accepted.

Apparel:

Master Carton dimensions to a maximun of 600 mm L x 400 mm H x 400 x mm W

Maximum weight 30 KGs. Per Master Carton

PRODUCT CARTON SPECIFICS

All saleable units must be delivered to QVC in mail order ready packaging. The vendor manual requires a product carton for all items bigger than **320mm length x 190mm width x 140mm.**

!ATTENTION! DO NOT USE THE PRODUCT LABEL TO CLOSE THE PRODUCT CARTON

Each must be individually saleable unit packed in a sealed clear and transparent polybag (minimum 40 micron) with label placed in the centre of the bag or right down (avoid to put the label on the polybag closure because in case of goods inspection the label should be broken). Logistic label must be apply on polybag, not on the hangtag.







Note: Any price must delete. No prices reported are allowed. If we receive goods with prices reported (on box, polybag, tag etc...), the rework will be necessary.


The closure of the product package must be ensure **always** with at least a piece of tape in order to avoid any kind of opening during the operations.



POLYBAG SPECIFICATION AND SUFFOCATION WARNING

Every polybag/product carton must be always closed. DO NOT USE THE LOGISTIC LABEL IN ORDER TO CLOSE THE POLYBAG!

Polybags should only be made of polyethylene (PE) or polypropylene (PP). <u>Transparent</u> and <u>colourless</u> **HDPE** (High Density Polyethylene) with a thick- ness of approximately **40 microns** must be used as material. The suffocation warning <u>must be applied</u> and <u>written in Italian</u> and contain the following statement or something substantially similar:





Even though few retailers demand a label warning of danger of suffocation, QVC wants to set a signal in this respect, as our customers' safety is very important to us. We have made a rule for this purpose and would like to request our suppliers to adhere to it.

Some plastic packaging films and polybags can pose a suffocation hazard for children. That is why QVC considers it necessary to mark some wrapping films and plastic bags with a warning to this effect. QVC's guidelines for notices warning of the danger of suffocation have been conceived to ensure the safety of products that can get into the hands of children.

Flexible plastic film bags (polybags) with all of the following dimensions require a suffocation warning:

- 1) An opening greater than 17 cm when placed flat.
- 2) An opening with a circumference greater than 35 cm when opened.
- 3) Nominal wall thickness less than 0.04 mm
- 4) A length greater than 35 cm.
- 5) A width greater than 20 cm.

Note: The warning is required only when the flexible plastic bag has all of the dimensions listed above. For example, if the circumference is 38 cm, but the bag is thicker than 0.04 mm, then a suffocation warning is not required or for example, if the sheet is less than 0.04 mm thick and the length is 38cm, but the width is only 17. cm, then a suffocation warning is not required.



The suffocation warning should be prominently visible to the customer. The warning should be printed on the bag or sheet, or on a pressure-sensitive label securely attached to the bag or sheet. If printed on the bag or sheet, the warning should be framed in a box. In either case, the print type should be boldface, clear and legible, and of a different typeface than the typeface used on other labels on the bag or sheet.

DROP TEST:

During the quality control (QC) inside the warehouse, a drop test will be carried on in order to verify that the product inside the packaging is not damaged during transport. This test involves a drop from a predetermined height on several faces of the product carton (for more details refer to italy.supplychain.vendormanual@qvc.com). In case of failure of the test, Vendor Compliance Team will contact the supplier to request that the packaging be reprocessed, charging him the cost. Fragile or spouted bottles and products must be packaged with special care.

PRESENTATION OF THE PACKAGING STRUCTURE:

The following possibilities exist for packing the goods in a box and on a pallet.

